



Nominal Bore of Flange	Outside Dia. of Appli - Cabele pipe	Inside Dia. of Flange do	Outside Dia. of Flange D	Sectional Dimensions of Flange					
				t	T	Dia. of Hub		Radius r	Raised Face f
						a	b		
10	17.3	17.8	90	12	-	-	-	-	1
15	21.7	22.2	95	12	-	-	-	-	1
20	27.2	27.7	100	14	-	-	-	-	1
25	34	34.5	125	14	-	-	-	-	1
32	42.7	43.2	135	16	-	-	-	-	2
40	48.6	49.1	140	16	-	-	-	-	2
50	60.5	61.1	155	16	-	-	-	-	2
65	76.3	61.1	155	16	-	-	-	-	2
80	89.1	77.1	175	18	-	-	-	-	2
90	101.6	90	185	18	-	-	-	-	2
(90)	114.3	102.6	195	18	-	-	-	-	2
100	139.8	115.4	210	18	-	-	-	-	2
125	165.2	141.2	250	20	-	-	-	-	2
150	190.7	166.6	280	22	-	-	-	-	2
(175)	216.3	192.1	305	22	-	-	-	-	2
200	241.8	218	330	22	-	-	-	-	2
(225)	267.4	218	330	22	-	-	-	-	2
250	318.5	243.7	350	22	-	-	-	-	2
300	355.6	269.5	400	24	36	288	292	6	2
350	406.4	321	445	24	38	340	346	6	3
400	457.2	358.1	490	26	42	380	386	6	3
450	508.0	409	560	28	44	436	442	6	3
500	558.8	460	620	30	48	496	502	6	3
550	609.6	511	675	30	48	548	554	6	3
600	660.4	562	745	32	52	604	610	6	3
650	711.2	613	795	32	52	656	662	6	3
700	762.0	664	845	34	56	706	712	6	3
750	812.8	715	905	34	58	762	770	6	3
800	863.6	766	970	36	62	816	824	6	3
850	914.4	817	1020	36	64	868	876	6	3
(850)	1016	868	1070	36	66	920	928	6	3
900	1117.6	919	1120	38	70	971	979	6	3
1000	1219.2	1021	1235	40	74	1073	1081	6	3
*(1100)	1371.6	1123	1345	42	76	-	-	-	3
*1200	1524.0	1225	1465	44	78	-	-	-	3
*1350		-	1630	48	82	-	-	-	3
*1500		-	1795	50	90	-	-	-	3

- (1) Flanges of parenthesized nominal diameter had letter not be used.
- (2) The facing of flanges shall conform to KS B1519(JIS B2202)1984.
- (3)Nominal diameter over 1000 is manufacturer's standard().